







The EBELCO 1200 series electromagnetic locks are renown with its excellent holding force and the remarkable features.

The series compliance to UL,CE and PSB Test are manufactured under the highest quality control to achieve the commitment to customer who always satisfied with maximum quality and reliability.



▶ Voltage Input: 12 VDC / 24 VDC

► Current Draw : 12V / 500mA ; 24V / 250mA (±5%)

► Holding Force : Up to 1200 lbs (545 kg)

- Hall Effect Contact : SPDT rated 2A at 24 VDC


Anti-Rust Surface Treatment : Blue Zinc Plating

Departing Temperature : 0~55° C (32~131° F)

- Operating Humidity : 0~95% (non condensing)

▶ Weight (Magnet) : 2.5 kg (±1%)

▶ **Dimensions**: Magnet - (L)266x(W)67x(T)39 mm Armature - (L)185x(W)61x(T)16.5 mm




IMPORTANT!

Set the jumper position according to the power input correctly before switch ON

FEATURES:

- Dual Voltage Selectable (12 VDC or 24 VDC)
- **Low Current Consumption**
- Reliable Holding Force
- **.** Hall Effect Sensor Monitoring Output
- ▶ Green/Red LED Indication for EM Lock Status
- **Durable and Silence Operation**
- Cosmeticize Anodized Aluminum Casing
- Surge & Spike Protection PCB
- Anti-Tamper Jam Nuts
- Full Range of Optional Brackets
- Anti Residual Magnetism Kick Off Button



EM Lock Energized

EM Lock De-energized

Disclaimer :

EBELCO reserve the right to go ahead with any modifications of models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication.

SECURITY

 \Box UALITY

RELIABILITY

EBELCO INDUSTRIES SENDIRIAN BERHAD

15, Jalan Cheng Perdana 1/4, Taman Cheng Perdana, 75050 Melaka, Malaysia. Website: www.ebelco.com; E-mail: enquiry@ebelco.com

Tel: 606-3122213 & Fax: 606-3122212

(C) Ebelco Copy Right 2006.