



© EBELCO COPYRIGHT 2019.

EMC-1112

HEAVY DUTY MAGNETIC
MAGNETIC CONTACT SENSOR

SPECIFICATION

BENEFITS

- Used for protecting sliding doors and windows where space is limited.
- Contact reed switch is SPST, Hermetically Sealed Switch, Rhodium Over Gold Reeds for a longer expected life.
- Unique epoxy compound protects reed switch.
- 3/8" Press-fit mount.

- $\varnothing 10 \times 18$ mm (L) : **Size**
- 28 VDC ; 0.5A ; 10W : **Max. Contact Rating**
- 8 gm : **Net Weight**
- White / Brown : **Colour Available**
- Normally Close (NC) : **Magnetic Contact Type**
- 22 mm ($\pm 5\%$) : **Sensor Range**
- Conceal Mounting : **Installation**
- 230 mm : **Wire Length**

EBELCO Concealed Magnetic Contact Sensor **EMC-1112** is specially designed for protecting sliding doors and windows where space is limited. The door contact sensor are suitable for central or standalone control monitoring systems. It can be used for closed circuit wiring. When the door open or circuit is open, the monitoring system will trigger instantly and vice versa.

The model is moulded with the highest engineering precision. The ABS material used is noted to be high resistance to heat and with good impact strength.

***Disclaimer :**

EBELCO reserve the right to go ahead with any modifications of the models or features or price without forewarning. All the information and specifications stated in this document are current at the time of publication.

CE **RoHS** **UL**



SECURITY . QUALITY . RELIABILITY

EBELCO INDUSTRIES SDN. BHD. 474704-V

16, Jalan TTC 26, Taman Teknologi Cheng,
75250, Melaka, Malaysia.

☎ : [+606] 333 8855 ☎ : [+606] 333 8822

🌐 : www.ebelco.com ✉ : enquiry@ebelco.com

WWW.EBELCO.COM